

Rubber Polymer Corporation  
1135 W. Portage Trail Ext., Akron, OH 44313-8283 USA  
Phone (800) 860-7721 \* Fax (330) 945-9416

MATERIAL SAFETY DATA SHEET (MSDS)

**MSDS FOR: PANTHER WATERPROOFING**

**DATE: June 1, 2006**

**SUPERSEDES: January 1, 2006**

**24 HOUR CHEMICAL  
EMERGENCY RESPONSE NUMBER:  
CHEM-TREC  
1-800-424-9300  
U.S.A and CANADA**

1. Identification:

Product Name: PANTHER WATERPROOFING

2. <u>Composition:</u>	Approximate Percentage
Asphalt	35-75
CAS 8052-42-4	
Polymer	5-25
Proprietary	
Emulsifier	0-5
Proprietary	
Water	25-35
CAS 7732-15-5	

3. Physical / Chemical Characteristics:

Appearance & Odor: Brown/Black

Specific Gravity: 1.0

Water Solubility: Dispersible

Percent Volatiles: None

Boiling Point: N/A

Vapor Density: N/A

4. Fire & Explosion Hazard Data:

Flash Point: >212 °F

Flammable Limits: LEL UEL  
N/A N/A

Fire Protection: Asphalt-emulsion liquid will not burn.

5. Health Hazard Data:

Exposure Limits: Avoid prolonged contact to skin.

6. Reactivity Data:

Stable: Yes

Conditions to Avoid: Avoid contact with strong oxidizing agents.

7. Precautions For Safe Handling & Use:

Keep product from freezing. Store sealed containers indoors at an ambient temperature above 50°F.

Avoid contact with eyes and skin.

Prevent inhalation and ingestion of vapors.

8. Special Protection Information:

Respiratory Protection: Wear NIOSH approved respirator

Eye Protection: Wear safety goggles

Skin: Wear protective clothing and impervious rubber gloves

9. Emergency and First Aid Measures:

Can cause headaches, nausea, dizziness, etc. Leave area immediately and breathe fresh air.

If ingested, seek medical attention.

Skin Contact: wash with soap and water.

Eye Contact: Rinse with water.

10. Disposal:

Dispose according to local and state regulations.

**24 HOUR CHEMICAL  
EMERGENCY RESPONSE NUMBER:  
1-800-424-9300  
U.S.A. and CANADA**